



CE

07
0338-CPD-1005
EN 14041:2004



SECTOR

Heavy Contract Carpet Tiles –Loop Pile

Specification:

100% Solution Dyed Nylon

Loop Pile

Tile Size: 500mm x 500mm
Total Thickness: 7.0mm
Pile Weight: 620g/m²
Total Weight: 4370g/m²
Tuft Density 180,780/m²
Suggested Laying Method: Broadloom/Tessellated/Random

Wear Characteristics



Castor Chair Test: BS EN 985: TEST A: 2001

Pass – Suitable for use in areas where castor chairs are used

Static Loading – BS 4939:1987(2003)

Recovery > 80%

Dynamic Load – BS ISO 2094:1999(2005)

Loss < 20%

Flame Resistance



Hot Metal Nut Test: BS 4790

Low radius of char -according to BS5287:1998 (1996)

BS EN 13501:2002

B_{fl}-s1

Colour Fastness



Shampoo: BS1006: UK-TB: 1990

Minimum grade 5

Light Fastness: BS1006: B2

Minimum grade 6

Static Protection



Antistatic and satisfying IBM/ICL requirements

Stroll Test: BS ISO 6356:2000

<2kV

September 2009

Burmatex are pleased to offer a 10-year guarantee on Sector, provided that it has been professionally fitted in accordance with the Burmatex Ltd. Installation Guide.