

technical specifications

Product Name	Axis
Product Description	Plain Twist Cut Pile
Pile Yarn Description	100% Nylon
Tile Dimensions	50 cm x 50 cm
Pile Yarn Weight	1170g/m ² +/-10%
Total Weight	5155g/m ² +/-10%
Pile Height	7.0mm +/-10%
Total Thickness	10.0mm +/-10%
Gauge/ends per 10cm	1/10th gauge 40 stitches
Tufts per m ²	157,480/m ² +/-10%
Backing Description	Bitumen composite, 70% recycled
Wear Classification	Heavy Contract
Flammability	Euroclass Bfl-s1
Castor Chair Rating	BS EN 985 Pass - suitable for continuous use
Hexapod	BS ISO 10361: Method B:2000
Static Loading	BS 4939:1987 (2003) Recovery >80% (24hrs)
Dynamic Loading	BS ISO 2094:1999 (2005) Loss <20% (1000 impacts)
Body Voltage Test	BS ISO 6356:2000 <2kV
Colour Fastness To Light	BS EN ISO 105 - B02 Minimum grade 5
Colour Fastness To Shampoo	BS 1006:UK-TB: 1990 Minimum Grade 4-5
Sound Absorption Coefficient	BS EN 354:2003
Reduction in Impact Noise	BS EN 140-8: Part 8: 1998 23dB
Number Of Tiles Per Box	16
BREEAM RATING	For specific ratings, please refer to www.bre.co.uk

*For further information on pricing and minimum order quantities for special dye options, please contact the Burmatex Sales Office



This floor covering was made with renewable electricity



Environmental Profiles Scheme
Certificate Number ENP353



Certificate Number FM01440
BS EN ISO 9001:2008

Burmatex Ltd,
Victoria Mills, The Green,
Ossett, West Yorkshire
WF5 OAN, United Kingdom

T +44 (0) 1924 262 525
F +44 (0) 1924 280 033
UK email: projects@burmatex.co.uk
International email: international@burmatex.co.uk
www.burmatex.co.uk

Burmatex reserve the right to improve the specification of all products without prior notification. E&OE