

## NBS Specification

### M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING

#### 15 CARPET TILING

**Balance**

A range of tiles manufactured using solution dyed nylon yarn in a loop pile construction. The yarn is tufted into a polyester scrim, a primary coat of resin is then applied followed by a modified bitumen backing a second polyester scrim is then laminated on to give extra strength and stability.

Size: 500 x 500mm. 600 x 600mm tiles can also be supplied to order.

Thickness: 7mm

Colour/pattern: Available in 18 colour ways.

Consult with Burmatex Ltd for technical details and to obtain samples.

**Preparation:** This item can usually be deleted when the base is new, for existing surfaces refer to Burmatex Ltd Installation literature.

**Fabricated underlay:** Plywood as clause 55. For use on timber floors only. Complete and include clause 55.

**Carpet tiles:**

**Manufacturer:** Burmatex Ltd, Victoria Mills, Ossett, West Yorkshire WF5 0AN Tel: 01924 262252 Fax 01924 280033 Email [info@burmatex.co.uk](mailto:info@burmatex.co.uk) Web: <http://www.nbsplus.co.uk/process.asp?Burmatex>

**Product reference:** Balance

Type: Tufted loop pile

BS EN 1307 classification Heavy Contract class 33

Size: 500 x 500 mm.

Colour/ pattern: Available in 18 different colours. Consult with manufacturers to obtain colours and samples.

**Method of laying:** Consult technical literature for installation details. Burmatex Ltd recommend Styccobond F3 adhesive for permanent fixing of tiles and Styccobond F41 for release systems – see F. Ball & Co Ltd NBS PLUS page for details.

**Accessories:** N/A