

NBS Specification

M50 RUBBER / PLASTICS / CORK / LINO / CARPET TILING / SHEETING

138 NEEDED CARPET TILING:

Academy Tile

Constructed from a blend of fine and coarse fibres comprising 15% nylon 85% polypropylene is needled with over 1 million needle punches per m² including a needling to form a textured wide rib cord. Latex is then applied, followed by modified bitumen backing, a polyester scrim is then laminated on to give extra strength and stability.

Size: 500 x 500mm. 600 x 600mm tiles can also be supplied to order.

Thickness: 7.8mm

Colour/pattern: Available in 32 colourways. Consult with manufacturers to obtain colours and samples and for technical details.

Consult Burmatex Ltd for technical details and to obtain samples.

Preparation: This item can usually be deleted when the base is new, for existing surfaces refer to Burmatex Ltd Installation literature.

Fabricated underlay: Plywood as clause 560. For use on timber floors only. Complete and include clause 560.

Carpet tiles:

Manufacturer: Burmatex Ltd, Victoria Mills, Ossett, West Yorkshire WF5 0AN Tel: 01924 262525 Fax 01924 280033 Email info@burmatex.co.uk Web: www.burmatex.co.uk

Product reference: Academy Tile

Type: Fibre Bonded

Heavy Contract

Size: 500 x 500 mm.

Colour/ pattern: Available in 32 different colours. Consult with manufacturers to obtain colours and samples.

Method of installation: Consult technical literature for installation details. Burmatex Ltd recommends Styccobond F3 adhesive for permanent fixing of tiles and Styccobond F41 for release systems – see F. Ball & Co Ltd NBS PLUS page for details.

Accessories: N/A