

## NBS Specification

### N10 GENERAL FIXTURES/FURNISHINGS/EQUIPMENT

#### 300 ENTRANCE MATTING:

##### **Chevrolay 50 Carpet Tile**

A carefully selected blend of coarse polypropylene needled from both sides with over two million needle punches per m<sup>2</sup> and then it is subjected to a further needling process which produces a chevron pattern. The product is then impregnated with a primary coat of resin followed by a modified bitumen backing, a second polyester scrim is then laminated on to give extra strength and stability

Size: 50cm x 50cm tile

Thickness: 12mm

Colour: Available in 5 colour ways.

Consult with Burmatex Ltd for technical details and to obtain samples.

**Manufacturer:** Burmatex Ltd, Victoria Mills, Ossett, West Yorkshire WF5 0AN Tel: 01924 2622525 Fax 01924 280033 Email [info@burmatex.co.uk](mailto:info@burmatex.co.uk) Web:

[www.burmatex.co.uk](http://www.burmatex.co.uk)

**Product reference:** Chevrolay 50 Carpet Tile

Type: Fibre Bonded

##### **Heavy Contract**

**Size:** 500 x500 mm

**Colour:** Available in 5 colour ways. Please contact manufacturer for details and samples.

**Method of installation:** Consult technical literature for installation details. Burmatex Ltd recommends Styccobond F3 adhesive for permanent fixing of tiles and Styccobond F41 for release systems – see F. Ball & Co Ltd NBS PLUS page for details.

**Accessories:** N/A