

# NBS Specification

## M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING

### 15 CARPET TILING

#### **Rialto**

A range of tiles manufactured using polypropylene fibres in a needle punch construction. Latex is then applied followed by a modified bitumen backing , a second polyester scrim is then laminated on to give extra strength and stability.

Size: 500 x 500mm.

Thickness: 7.8mm

Colour/pattern: Available in 12 colour ways.

Consult with Burmatex Ltd for technical details and to obtain samples.

**Preparation:** This item can usually be deleted when the base is new, for existing surfaces refer to Burmatex Ltd Installation literature.

**Fabricated underlay:** Plywood as clause 55. For use on timber floors only. Complete and include clause 55.

#### **Carpet tiles:**

**Manufacturer:** Burmatex Ltd, Victoria Mills, Ossett, West Yorkshire WF5 0AN Tel: 01924 262252 Fax 01924 280033 Email [info@burmatex.co.uk](mailto:info@burmatex.co.uk) Web: <http://www.nbsplus.co.uk/process.asp?Burmatex>

**Product reference:** Rialto

Type: Fibre-bonded Needle punch product

#### **Heavy Contract**

**Size:** 500 x 500 mm.

**Colour/ pattern:** Available in 12 different colours. Consult with manufacturers to obtain colours and samples.

**Method of Installation:** Consult technical literature for installation details. Burmatex Ltd recommends Styccobond F3 adhesive for permanent fixing of tiles and Styccobond F41 for release systems – see F. Ball & Co Ltd NBS PLUS page for details.

**Accessories:** N/A