

NBS Specification

M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING

15 CARPET TILING

Tivoli 24

A range of tiles manufactured using 100% premium polypropylene in a low level loop pile construction. The yarn is tufted into a polyester scrim, a primary coat of resin is then applied followed by a modified bitumen backing, a second polyester scrim is then laminated on to give extra strength and stability.

Size: 500 x 500mm. 600 x 600mm tiles can also be supplied to order.

Thickness: 6.9mm

Colour/pattern: Available in 24 colour ways.

Consult with Burmatex Ltd for technical details and to obtain samples.

Preparation: This item can usually be deleted when the base is new, for an existing surface refer to Burmatex Ltd Installation literature.

Fabricated underlay: Plywood as clause 55. For use on timber floors only. Complete and include clause 55.

Carpet tiles:

Manufacturer: Burmatex Ltd, Victoria Mills, Ossett, West Yorkshire WF5 0AN Tel: 01924 262252 Fax 01924 280033 Email info@burmatex.co.uk Web: <http://www.nbsplus.co.uk/process.asp?Burmatex>

Product reference: Tivoli 24

Type: Tufted loop pile

Heavy Contract

Size: 500 x 500 mm.

Colour/ pattern: Available in 24 different colours. Consult with manufacturers to obtain colours and samples.

Method of laying: Consult technical literature for installation details. Burmatex Ltd recommend Styccobond F3 adhesive for permanent fixing of tiles and Styccobond F41 for release systems – see F. Ball & Co Ltd NBS PLUS page for details.

Accessories: N/A