

SPIN TILES

Heavy Contract Carpet Tiles – Textured Loop Pile

Specification:

100% Aquafil Alto-Chroma Solution Dyed Nylon

Tile Size: 500mm x 500mm
 Total Thickness: 7.5mm
 Pile thickness: 4.5mm
 Pile Weight: 750g/m²
 Total Weight: 4365g/m²
 Tuft Density 212,600/m²
 Suggested Laying Method: Broadloom or Tessellated

Wear Characteristics



Castor Chair Test: BS EN 985: TEST A: 2001

Pass – Suitable for use in areas where castor chairs are used

Static Loading – BS 4939:1987(2003)

Recovery > 85%

Dynamic Load – BS ISO 2094:1999(2005)

Loss < 15%

Flame Resistance



Hot Metal Nut Test: BS 4790

Low radius of char -according to BS5287:1998 (1996)

BS EN 13501:2002

B_{fl}-s1

Colour Fastness



Shampoo: BS1006: UK-TB: 1990

Minimum grade 5

Light Fastness: BS EN ISO 105- B2:1999

Minimum grade >6



Static Protection

Stroll Test: BS ISO 6356:2000(2005)

<2kV

August 2007

All Burmatex tile products contain up to 10% of post-manufacture recycled waste in the tile backings.

SPIN tiles can be laid broadloom or tessellated.

Burmatex are pleased to offer a 10-year guarantee on SPIN, provided that it has been professionally fitted in accordance with the Burmatex Ltd. Installation Guide.