

technical specifications

Product Name	Tivoli Online
Product Description	Low Level Loop
Pile Yarn Description	100% Premium Polypropylene
Tile Dimensions	50 cm x 50 cm
Pile Yarn Weight	600g/m ² +/-10%
Total Weight	4040g/m ² +/-10%
Pile Height	4.4mm +/-10%
Total Thickness	6.9mm +/-10%
Gauge/ends per 10cm	1/10th gauge 50 stitches
Tufts per m2	212,760/m ² +/-10%
Backing Description	Bitumen composite, 70% recycled
Flammability	Euroclass Bfl-s1
Castor Chair Rating	BS EN 985 Pass - suitable for continuous use
Hexapod	BS ISO 10361: Method B:2000
Body Voltage Test	BS ISO 6356:2000 <2kV
Colour Fastness To Light	BS EN ISO 105 - B02 Minimum grade 6
Colour Fastness To Shampoo	BS 1006:UK-TB: 1990 Minimum Grade 4
Sound Absorption Coefficient	BS EN 354:2003
Reduction in Impact Noise	BS EN 140-8: Part 8: 1998 21dB
Number Of Tiles Per Box	20
BREEAM RATING	For specific ratings, please refer to www.bre.co.uk



This floor covering was made with renewable electricity



Environmental Profiles Scheme
Certificate Number ENP353



Burmatex Ltd,
Victoria Mills, The Green,
Ossett, West Yorkshire
WF5 OAN, United Kingdom

T +44 (0) 1924 262 525
F +44 (0) 1924 280 033
UK email: projects@burmatex.co.uk
International email: international@burmatex.co.uk
www.burmatex.co.uk

Burmatex reserve the right to improve the specification of all products without prior notification. E&OE