

## VIBE TILES

### Heavy Contract Carpet Tiles – Textured Cut & Loop Pile

#### Specification:

100% Aquafil Alto-Chroma Solution Dyed Nylon

Tile Size: 500mm x 500mm  
 Total Thickness: 8.0mm  
 Pile Thickness: 5.0mm  
 Pile Weight: 780g/m<sup>2</sup>  
 Total Weight: 4395g/m<sup>2</sup>  
 Tuft Density: 212,600/m<sup>2</sup>  
 Suggested Laying Method: Broadloom or Tessellated

#### Wear Characteristics



**Castor Chair Test: BS EN 985: TEST A: 2001**

**Pass** – Suitable for use in areas where castor chairs are used

**Static Loading – BS 4939:1987(2003)**

Recovery > 85%

**Dynamic Load – BS ISO 2094:1999(2005)**

Loss < 15%

#### Flame Resistance



**Hot Metal Nut Test: BS 4790**

Low radius of char -according to BS5287:1998 (1996)

**BS EN 13501:2002**

B<sub>fl</sub>-s1

#### Colour Fastness



**Shampoo: BS1006: UK-TB: 1990**

Minimum grade 5

**Light Fastness: BS EN ISO 105- B2:1999**

Minimum grade >6

#### Static Protection



**Stroll Test: BS ISO 6356:2000(2005)**

<2kV

**August 2007**

All Burmatex tile products contain up to 10% of post-manufacture recycled waste in the tile backings.

VIBE tiles can be laid broadloom or tessellated.

Burmatex are pleased to offer a 10-year guarantee on VIBE, provided that it has been professionally fitted in accordance with the Burmatex Ltd. Installation Guide.