

# technical specifications

Product Name	Code
Product Description	Heavy Contract Carpet Tiles
Pile Yarn Description	85% Polypropylene 15% Nylon
Tile Dimensions	50 cm x 50 cm
Pile Weight	1000g/m <sup>2</sup> +/-10%
Total Weight	4250g/m <sup>2</sup> +/-10%
Total Thickness	8.0mm +/-10%
Backing Description	Bitumen composite, 70% recycled
Flammability	Euroclass Bfl-s1
Castor Chair Rating	BS EN 985 Pass - suitable for continuous use
Static Loading	BS 4939: 1987 (2003) Recovery >80% (24hrs)
Dynamic Loading	BS ISO 2094: 1999 (2005) Loss <20% (1000 impacts)
Body Voltage Test	BS ISO 6356:2000 <2kV
Colour Fastness To Light	BS EN ISO 105 - B02 Minimum grade 6
Colour Fastness To Shampoo	BS 1006:UK-TB: 1990 Minimum Grade 5
Sound Absorption Coefficient	BS EN 354:2003
Reduction in Impact Noise	BS EN 140-8: Part 8: 1998 17dB
Number Of Tiles Per Box	20
BREEAM RATING	For specific ratings, please refer to <a href="http://www.bre.co.uk">www.bre.co.uk</a>



This floor covering was made with renewable electricity



Environmental Profiles Scheme  
Certificate Number ENP353



Burmatex Ltd,  
Victoria Mills, The Green,  
Ossett, West Yorkshire  
WF5 OAN, United Kingdom

T +44 (0) 1924 262 525  
F +44 (0) 1924 280 033  
UK email: [projects@burmatex.co.uk](mailto:projects@burmatex.co.uk)  
International email: [international@burmatex.co.uk](mailto:international@burmatex.co.uk)  
[www.burmatex.co.uk](http://www.burmatex.co.uk)

Burmatex reserve the right to improve the specification of all products without prior notification. E&OE