



# technical specifications

Product Name	Tandem
Product Description	Textured Loop Pile
Pile Yarn Description	100% Solution Dyed & Space Dyed Nylon (Polyamide-PA)
Tile Dimensions	50 cm x 50 cm
Pile Yarn Weight	620g/m <sup>2</sup>
Total Weight	4370g/m <sup>2</sup>
Pile Height	3.5mm
Total Thickness	6mm
Gauge/ends per 10cm	1/10 <sup>th</sup> - 60 stitches
Tufts per m <sup>2</sup> / Pile Density	235,800/m <sup>2</sup>
Backing Description	Accummen™, 75% recycled
Wear Classification	BS EN 1307 Heavy Commercial Use Class 33
Luxury Rating Class	LC1
Flammability	Euroclass Bfl-s1
Thermal Resistance	Tog Rating 0.32; ISO 8302: 0.04 m <sup>2</sup> K/W
Castor Chair Rating	BS EN 985 Pass - suitable for continuous use
Hexapod	BS ISO 10361: Method B:2000 3 to 4
Static Loading	BS 4939:1987 (2003) Recovery >80% (24hrs)
Dynamic Loading	BS ISO 2094:1999 (2005) Loss <20% (1000 impacts)
Body Voltage Test	BS ISO 6356:2000 <2kV
Colour Fastness To Light	BS EN ISO 105 - B02 Minimum Grade 6
Colour Fastness To Shampoo	BS 1006:UK-TB: 1990 Minimum Grade 4-5
Reduction in Impact Noise	BS EN ISO 10140-3:2010 20dB
Reduction in Impact Noise at 1000Hz	BS EN ISO 10140-3:2010 27.4dB
Number Of Tiles Per Box	20 (5m <sup>2</sup> )

For best results we recommend



Monolithic



Quarter Turn



This floor covering was made with renewable electricity



Certificate Number FM01440  
BS EN ISO 9001:2015



Statement on level of emission of volatile substances in indoor air posing a toxic threat during inhaling - on a scale from A+ (very low-emission) to C (high-emission)



The Building Information Foundation, Finland. Certified building materials with low emission class M1

## environmental information

- burmatex® products qualify for SKA as they achieve one or more requested criteria
- burmatex® products can contribute to the WELL Building Standard™, which focuses on the people and healthy workspaces
- All burmatex® carpet/carpet tile/carpet plank ranges are made at its single UK manufacturing site
- Wherever possible, raw materials including yarn/fibre are sourced locally i.e. within 20 miles
- Over 75% of burmatex® Accummen™ backing comes from recycled materials
- Continuous assessment and improvement of manufacturing process to minimise use of raw materials/power
- All manufacturing waste is recycled and all electricity used is from renewable resources
- All burmatex® products are heavy contract with a 10 year guarantee for maximum useful life
- Certified, Class A+: very-low VOC Emission

**LEED® v4** - Burmatex products can contribute towards satisfying the following credits for LEED v4: NC-v4/CI-v4 MRc2/MRc3 (Building product disclosure and optimization - environmental product declarations), MRc3/MRc4 (Building product disclosure and optimization - sourcing of raw materials), EQc1 (Enhanced indoor air quality strategies), EQc2 (Low-emitting materials), EQc6 (Interior lighting - Option 2. Lighting quality (E - H)) and EQc9 (Acoustic Performance). Products are not reviewed under LEED. LEED credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information on LEED, visit [www.usgbc.org/contact](http://www.usgbc.org/contact)

Burmatex Ltd  
Victoria Mills, The Green  
Ossett, West Yorkshire  
WF5 OAN  
United Kingdom

T +44 (0) 1924 262 525  
F +44 (0) 1924 280 033  
UK email: [projects@burmatex.co.uk](mailto:projects@burmatex.co.uk)  
International email: [international@burmatex.co.uk](mailto:international@burmatex.co.uk)  
[www.burmatex.co.uk](http://www.burmatex.co.uk)

Burmatex reserves the right to improve the specification of all products without prior notification. E&OE  
Burmatex carpets, carpet tiles & carpet planks should be installed and used in full accordance with instructions at [www.burmatex.co.uk](http://www.burmatex.co.uk) and recognised trade standards.  
Orders are subject to Burmatex terms and conditions of sale.  
See: [www.burmatex.co.uk](http://www.burmatex.co.uk)

## LRV values for **tandem**

<b>Product code</b>	<b>Product colour name</b>	<b>CIE Y</b>	<b>CIE L</b>
19801	galvanised steel	9.61	37.13
19802	blue tin	8.56	35.12
19803	warmed lead	8.44	34.88
19804	permanganate	7.44	32.78
19805	burnished copper	9.38	36.71
19806	green nickel	8.73	35.46