



technical specifications

Product Name	Grimebuster 50
Product Description	Fibre Bonded
Pile Yarn Description	100% Polypropylene
Tile Dimension	50cm x 50cm
Pile Weight	1490g/m ²
Total Weight	4300g/m ²
Total Thickness	12mm
Backing Description	Accummen™, 75% recycled
Wear Classification	Heavy Contract
Flammability	Euroclass Bfl-s1
Colour Fastness To Light	BS EN ISO 105 - B02 Minimum grade 6
Colour Fastness To Shampoo	BS 1006:UK-TB: 1990 Minimum Grade 4
Number of Tiles per Box	12 (3m ²)

For best results
we recommend



Quarter Turn



This floor covering was made
with renewable electricity



Certificate Number FM01440
BS EN ISO 9001:2015



THE INTERNATIONAL EPD® SYSTEM

Environmental Product
Declaration by independent
third-party verification of the
declaration and data, according
to ISO 14025:2006

environmental information

- burmatex® products are EPD verified by an independent third-party verification of the declaration and data, according to ISO 14025:2006. For specific ratings, please refer to www.environdec.com
- burmatex® products qualify for SKA as they achieve one or more requested criteria
- burmatex® products can contribute to the WELL Building Standard™, which focuses on the people and healthy workspaces
- All burmatex® carpet/carpet tile/carpet plank ranges are made at its single UK manufacturing site
- Wherever possible, raw materials including yarn/fibre are sourced locally i.e. within 20 miles
- Over 75% of burmatex® Accummen™ backing comes from recycled materials
- Continuous assessment and improvement of manufacturing process to minimise use of raw materials/power
- All manufacturing waste is recycled and all electricity used is from renewable resources
- All burmatex® products are heavy contract with a 10 year guarantee for maximum useful life

LEED® v4 - Burmatex products can contribute towards satisfying the following credits for LEED v4: NC-v4/Ci-v4 MRc2/MRc3 (Building product disclosure and optimization - environmental product declarations), MRc3/MRc4 (Building product disclosure and optimization - sourcing of raw materials), EQc1 (Enhanced indoor air quality strategies), EQc2 (Low-emitting materials), EQc6 (Interior lighting - Option 2. Lighting quality (E - H)) and EQc9 (Acoustic Performance). Products are not reviewed under LEED. LEED credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information on LEED, visit www.usgbc.org/contact

Burmatex Ltd
Victoria Mills, The Green
Ossett, West Yorkshire
WF5 0AN
United Kingdom

T +44 (0) 1924 262 525
F +44 (0) 1924 280 033
UK email: projects@burmatex.co.uk
International email: international@burmatex.co.uk
www.burmatex.co.uk

Burmatex reserves the right to improve the specification of all products without prior notification. E&OE

Burmatex carpets and carpet tiles should be installed and used in full accordance with instructions at www.burmatex.co.uk and recognised trade standards.

Orders are subject to Burmatex terms and conditions of sale. See: www.burmatex.co.uk

LRV values for **grimebuster 50**

Product code	Product colour name	CIE Y	CIE L
1628	haydock blue	2.85	19.43
1636	curragh green	2.36	17.27
1639	goodwood brown	2.62	18.45
1640	newmarket grey	3.52	22.00
1646	wincanton fawn	4.34	24.78