## origin carpet tiles

## Burmatex® MANUFACTURERS OF CREATIVE FLOORING

## technical specifications

Parm
Dimensions
Pile Weight
Total Weight
Pile Height
Total Thickness
Construction
Pile Density
Backing

Backing Wear Classification Luxury Rating Class Flammability Thermal Resistance Castor Chair Rating

Hexapod
Static Loading
Dynamic Loading
Body Voltage Test
Colour Fastness To Light
Colour Fastness To Shampoo
Sound Absorption Coefficient
Reduction in Impact Noise
Reduction in Impact Noise at 1000Hz

VOC Warranty

Number Of Tiles Per Box

100% Econyl® regenerated recyclable solution dyed nylon

50cm x 50cm 1300g/m<sup>2</sup> 4550g/m<sup>2</sup> 7.0mm 9.5mm

Tufted 1/10th gauge cut pile twist

165.354/m<sup>2</sup>

BioBase® recycled backing (recycled BS EN ISO 14021)

Class 33 heavy commercial use (BS EN 1307)

LC5 Euroclass Bfl-s1 Tog Rating 0.93

BS EN 985 Pass - suitable for continuous use

BS ISO 10361: Method B:2000 3 to 4

BS 4939: 1987 (2003) Recovery >80% (24hrs) BS ISO 2094: 1999 (2005) Loss <20% (1000 impacts)

BS ISO 6356:2000 <2kV

BS EN ISO 105 - B02 Minimum Grade 6 BS 1006:UK-TB: 1990 Minimum Grade 4-5

BS EN 354:2003

BS EN ISO 10140-3:2010 28dB BS EN ISO 10140-3:2010 47.0dB

A+ 15 years 14 (3.5m<sup>2</sup>)











quarter turn



We are committed to helping deliver a sustainable future, because we believe that what we do **matters**. To help us deliver on this commitment, we have developed **ecommitters**\*, our sustainability principles, supported by independent 3rd party verification.



Journey to Net Zero & Bevond



Positive Environmental Impact



Social Values & Well Being

Made from 100% Econyl® regenerated recyclable solution dyed nylon yarn and our unique BioBase® recycled backing, origin is low carbon. The commercial colour palette of 10 is sophisticated and refined, inspired by coastal walks and views. This cut pile range works both as a stand-alone product, and with others from our product portfolio, to enhance any commercial setting.



origin is low carbon



BioBase® backing

origin is made from 100% Econyl® regenerated recyclable yarn

I FFD

origin uses BioBase® recycled backing







SKA
Burmatex® products
adhere to SKA standards

Burmatex® reco<sup>®</sup>very take back service provides a no landfill solution for your used tiles

**Burmatex**\* products are made using 100% certified **renewable** electricity

eco matters declarations are independently 3rd party verified

WELL Building Standards Burmatex® products contribute to WELL Building Standards



**Burmatex**<sup>®</sup> products are supported by 3rd party independently verified, product specific EPD's



need a BIM object?

**Burmatex**® products

contribute towards Leed

all our products have BIM objects available on our website

accreditation

need samples? scan the QR code visit www. burmatex.co.uk call +44 (0) 1924 262525 email samples@burmatex.co.uk



contact us T +44 (0) 1924 262 525 email: sales@burmatex.co.uk Burmatex Ltd Victoria Mills, The Green Ossett, West Yorkshire WF5 OAN, United Kingdom





## LRV values

Product code	Product colour name	CIE Y
33201	cloud	20.75
33202	pearl	18.49
33203	pebble	10.58
33204	shale	7.67
33205	mussel	5.24
33206	gull	2.57
33207	gorse	12.86
33208	surf	6.82
33209	wave	2.10
33210	heather	4.16

