


**technical specifications**

|   |   |
|---|---|
| Product Description                     | <b>Low Carbon</b> Level Loop                                |
| Pile Yarn Description                   | <b>EgoCycle<sup>®</sup> 75 recycled</b> solution dyed nylon |
| Tile Dimensions                         | 50cm x 50cm   |
| Pile Yarn Weight                        | 500g/m <sup>2</sup>   |
| Total Weight                            | 3810g/m <sup>2</sup>  |
| Pile Height                             | 3.0mm   |
| Total Thickness                         | 5.5mm   |
| Construction                            | Tufted 1/10th gauge loop                                    |
| Tufts per m <sup>2</sup> / Pile Density | 196,850/m <sup>2</sup>                                      |
| Backing Description                     | <b>BioBase<sup>®</sup></b> backing (recycled EN 14021)      |
| Wear Classification                     | class 33 heavy commercial use (BS EN 1307)                  |
| Luxury Rating Class                     | LC1   |
| Flammability                            | Euroclass Bfl-s1  |
| Thermal Resistance                      | Tog Rating: 0.42  |
| Castor Chair Rating                     | BS EN 985 Pass - suitable for continuous use                |
| Hexapod                                 | BS ISO 10361: Method B:2000 3 to 4                          |
| Static Loading                          | BS 4939: 1987 (2003) Recovery >80% (24hrs)                  |
| Dynamic Loading                         | BS ISO 2094: 1999 (2005) Loss <20% (1000 impacts)           |
| Body Voltage Test                       | BS ISO 6356:2000 <2kV                                       |
| Colour Fastness To Light                | BS EN ISO 105 - B02 Minimum Grade 6                         |
| Colour Fastness To Shampoo              | BS 1006:UK-TB: 1990 Minimum Grade 4-5                       |
| Sound Absorption Coefficient            | BS EN 354:2003  |
| Reduction in Impact Noise               | BS EN ISO 10140-3:2010 20dB                                 |
| Reduction in Impact Noise at 1000Hz     | BS EN ISO 10140-3:2010 28.5dB                               |
| Number Of Tiles Per Box                 | 20 (5m <sup>2</sup> )                                       |
| VOC                                     | Class A+  |
| Warranty                                | 15 years  |

go to



monolithic



quarter turn

go to stripe



brick



quarter turn



**eco<sub>2</sub>matters**<sup>®</sup>

We are committed to helping deliver a sustainable future, because we believe that what we do **matters**. To help us deliver on this commitment, we have developed **eco<sub>2</sub>matters**<sup>®</sup> sustainability goals, supported by the independently 3rd party verified **eco<sub>2</sub>matters**<sup>®</sup> ecosystem.



**Journey to Net Zero & Beyond**



**Positive Environmental Impact**



**Social Values & Well Being**

Made from **EgoCycle<sup>®</sup> 75 recycled** solution dyed nylon, and our unique **BioBase<sup>®</sup> recycled** backing, **go to**<sup>®</sup> delivers class 33 Heavy Commercial Use performance at unrivalled value. Supported by high stock levels, and rapid delivery, the 20 colour palette of coordinating plains and stripes provides versatility for use in any space.



**go to**<sup>®</sup> is **low carbon**



**go to**<sup>®</sup> uses **EgoCycle<sup>®</sup> 75 recycled** yarn



**go to**<sup>®</sup> uses **BioBase<sup>®</sup> recycled** backing



**Burmatex<sup>®</sup> reco<sub>2</sub>very** take back service provides a no landfill solution for your used tiles



**Burmatex<sup>®</sup>** products are made using 100% certified **renewable** electricity



**eco<sub>2</sub>matters**<sup>®</sup> ecosystem is independently 3rd party verified

**EPD**  
our products are supported by a 3rd party verified EPD

**LEED**  
our products contribute towards Leed accreditation

**SKA**  
our products adhere to SKA standards

**WELL Building Standards**  
Our products contribute to WELL Building Standards

contact us  
T +44 (0) 1924 262 525  
F +44 (0) 1924 280 033  
email: [projects@burmatex.co.uk](mailto:projects@burmatex.co.uk)

Burmatex Ltd  
Victoria Mills, The Green  
Ossett, West Yorkshire  
WF5 0AN, United Kingdom

[www.burmatex.co.uk](http://www.burmatex.co.uk)

## LRV values

| Product code | Product colour name | CIE Y |
|--------------|---------------------|-------|
| 21801        | jet black           | 3.01  |
| 21802        | coal grey           | 5.21  |
| 21803        | medium grey         | 9.19  |
| 21806        | sea blue            | 6.45  |
| 21810        | sky blue            | 12.13 |
| 21811        | green               | 16.80 |
| 21813        | light beige         | 21.14 |
| 21814        | medium beige        | 13.20 |
| 21815        | dark beige          | 9.07  |
| 21816        | metal grey          | 6.27  |
| 21817        | light grey          | 13.98 |
| 21818        | moss green          | 12.53 |
| 21819        | orange              | 12.04 |
| 21820        | red                 | 4.68  |
| 21821        | purple              | 6.67  |
| 21822        | deep blue           | 5.74  |
| 21902        | coal grey stripe    | 10.36 |
| 21903        | medium grey stripe  | 6.49  |
| 21906        | sea blue stripe     | 4.83  |
| 21915        | dark beige stripe   | 6.03  |